

FLOW METERS

Simple to operate, easy to install and requires no maintenance



without valve with valve

Panel Mount Flow Meter

Features

- Acrylic flow meter with stainless steel float
- 1/2" BSPT male thread for easy installation and mounting on panel
- Easy to read with accuracy $\pm 4\%$
- Working pressure < 10 bar
- Working temperature < 60°C
- Option of adjustable valve to control flow rate

| Part No. | Measurement | |
|---------------------------|-------------|-------------------------|
| FFM15-18L (without valve) | 0.5-5 GPM | 2-18 LPM |
| FFM15V-18L (with valve) | 0.5-5 GPM | 2-18 LPM |
| FFM15-1M (without valve) | | 0.1-1 m ³ /h |
| FFM15V-1M (with valve) | | 0.1-1 m ³ /h |

In-line Flow Meter

Features

- All plastic tube flow meter. No metal parts in fluid path.
- Designed for in-line installation (vertical)
- Easy to read with accuracy $\pm 4\%$
- Working pressure < 6 bar
- Working temperature < 60°C

| Part No. | Type | Measurement | Diameter (DN) mm |
|--------------|------------|--------------------------|------------------|
| FFM15-600LL | Long tube | 60-600 LPH | 15 |
| FFM25-1000LL | Long tube | 100-1000 LPH | 25 |
| FFM25-2500LL | Long tube | 250-2500 LPH | 25 |
| FFM32-6MS | Short tube | 0.6-6 m ³ /h | 32 |
| FFM50-6ML | Long tube | 0.6-6 m ³ /h | 50 |
| FFM50-16ML | Long tube | 1.6-16 m ³ /h | 50 |



long tube short tube

Note: UltraPure Private Limited reserves the right to make any changes to the information provided above without prior notice



ULTRAPURE PRIVATE LIMITED 122 Joo Chiat Road, Singapore 427411
Tel: (65) 64403680 Fax: (65) 64403679 Email: info@ultrapure.com.sg Website: www.ultrapure.com.sg