ULTRAPURE COUNTER TOP DISPENSER REVERSE OSMOSIS SYSTEM

- A compact and practical water dispenser with 4 stage treatment.
- Ideal for home, office pantry, waiting rooms or where space is at a premium.



Reverse Osmosis (RO) membrane removes:

- ✓ Fluoride
- ✓ Arsenic
- Bacteria
- ✓ Virus
- ✓ Salt
- ✓ Microbial Contaminants

Specification

RO Membrane	Thin film spiral wound
Flow rate	50 gpd*
Max. pressure	100 psi
Min. pressure	40 psi
Max. TDS	2,000 ppm
Tank	3.2 gallons (12 litres)
Tubing	1/4"
Power	220V
Dimensions, approximate	35 x 30 x 45 cm

Features & Benefits

- Four stage treatment for superior performance
- Flow rate of 50 gpd*
- Booster pump for proper pressure requirements (power socket required)
- Small footprint
- Easy installation
- Auto cut-off valve, ¼" tubing, connectors

UltraPure 4 stage RO dispenser system:

Stage #1: Sediment pre-filter to reduce sediment, dirt, rust particles, silt and suspended matter. Recommended change every 3 - 6 months.

Stage #2: Carbon pre-filter to reduce chlorine, organic chemicals, bad taste and odours. Recommended change every 6 months.

Stage #3: RO membrane to remove bacteria and virus, and reduce dissolved solids and contaminants. Recommended change every 1 - 2 years.

Stage #4: Carbon post-filter to remove odour and improve taste. The permeate or filtered water is stored in the tank of the dispenser. Recommended change every 1 year.

Note: UltraPure Private Limited reserves the right to make any changes to the information provided above without prior notice



^{*} US gallons per day.