ULTRAPURE FILTER HOUSINGS

Durable, High Quality housings for all your water filtration needs!



Features & Benefits

- High quality FDA grade polypropylene (PP) / polycarbonate (PC) and Acrylonitrile butadiene styrene (ABS) material.
- Rubber o-ring located in housing sump provides leak-proof seal.
- Thick wall and ribs strengthen housing making it ideal for a wide range of applications.
- Housings supplied with and without pressure release valves.
- Temperature rated to 100°F (50°C).
- Pressure rated to 90 psi (6.3 bar).
- Available in colour and clear models, different caps and pipe sizes.
- Housings fit standard filter cartridges / elements.

Specification

Material , sump & cap	PP / PC and ABS
Material , o-ring	EPDM
Max. temperature	100°F / 50°C
Max. pressure	90 psi / 6.3 bar
Size & type	10", 20" Standard (slim) 10", 20" Full-flow (B-B)
Pipe size	1/4", 1/2", 3/4", 1", 1-1/2"

^{*}Flow rate and pressure loss depend on type of filter cartridge / element used

Housing accessories available:



Note: UltraPure Private Limited reserves the right to make any changes to the information provided above without prior notice



ULTRAPURE PRIVATE LIMITED 122 Joo Chiat Road, Singapore 427411 Tel: (65) 64403680 Fax: (65) 64403679 Email: info@ultrapure.com.sg Website: www.ultrapure.com.sg